

Light fittings with protection guard, brass, 3314, up to T4, max. 200W, Ignition protection 'd'



- Explosion protection:** II 2G Ex d IIC
Zone: 1
Certificates: PTB 07 ATEX 1008 X
Protection class to EN 60 529: IP 67
Ambient temperature: -25°C up to +45°C
Temperature class:
 - Incandescent lamp up to 200W/230V = hanging T4, any T3
 - Compact fluorescent lamp up to 23W/230V = hanging T4, any T3
Material: Red brass
Lamp:
 - Incandescent lamp up to 200W
 - Compact fluorescent lamp up to 23W
 (lamps not included in delivery)
 Only lamps approved by the EC-type-examination certificate have to be used (see operating instruction).
Equipment:
 - Delivery without cable glands
 - The volume of the light fitting 3314 exceeds 2 litres. For flameproof enclosures cable entries have to be selected according to EN 60079-14 (see Technical Principles). Outside the EU please attend to national regulations.
 - Appropriate cable glands on request

| Type | Lampholder |
|----------|------------|
| 3314/E27 | E 27 |

Accessories / Spare parts

Compact fluorescent lamps

| Type | Description | Suitable for |
|-------|---|--------------|
| ES 23 | Compact fluorescent lamp, E27, 230V / 23W / 50/60Hz | 3312 |

Glasses, Protection guards

| Type | Description | Suitable for |
|----------|--|--------------|
| 3351/Gew | Spare glass with wire guard, Brass/red brass, glass ring with thread | 3312 |

Sockets

| Type | Description | Suitable for |
|----------|-------------------------------------|--------------|
| 1974/BRS | Two-pin holder E27, vibration-proof | 3312 |

Tools for Ex-proof devices

| Description | Suitable for |
|--------------------------|--------------|
| Inner hexagonal key 4 mm | 3312 |
| Inner hexagonal key 5 mm | 3312 |
| Rotary lever | 3312 |