











- Protection class to EN 60 529:** IP 66 / 67  
**Flame protection:** Glow wire test 750° C acc. to EN 60695-2-11  
**Temperatures during installation:** -5°C to 60°C  
**Temperature range of material:** -30°C to 100°C, intermittent up to approx. 120°C  
**Voltage:** 690 V  
**Material:** Polypropylene, reinforced glass fibre; sealing: thermoplastic elastomere  
**Terminals/poles:** 6 mm<sup>2</sup>  
**Fixing:** 4 internal openings outside of the sealing area  
**Equipment:** Elastic self-sealing membranes for cable entry without mechanical devices: 7 inlets at the side and 3 inlets in the base  
 - 7 integrated M 25 threads, no locknuts necessary  
 - 4 captive quick-release lid screws  
 - Colour RAL 7035 light grey  
 - .../S = black  
 - .../W = white  
 - .../ESKV incl. 3 pcs. ESKV M 25 (\*Sealing range 9 - 17 mm)
- Accessories:**  
 - DIN RAIL KIT 607: Rail TS 35 + Fixing material, WISKA-No. 10060361  
 - EC 607 Earthing plate: WISKA No. 10101474

Type	WISKA-No.		 mm		L x B x H external / außen mm
COMBI 607/leer	10060531	3/27	3 - 17		110 x 110 x 66
COMBI 607/leer/S	10060648	3/27	3 - 17		110 x 110 x 66
COMBI 607/leer/W	10060533	3/27	3 - 17		110 x 110 x 66
COMBI 607/ESKV	10060529	3/27	3 - 17*		110 x 110 x 66
COMBI 607/5	10060532	3/27	3 - 17		110 x 110 x 66
COMBI 607/5/S	10060538	3/27	3 - 17		110 x 110 x 66
COMBI 607/5/W	10060534	3/27	3 - 17		110 x 110 x 66
DIN RAIL KIT 607	10060361	1	—	—	—