



- Protection class to EN 60 529:** IP 66 / 67
- Flame protection:** Glow wire test 750° C acc. to EN 60695-2-11
- Temperatures during installation:** -5°C to 60°C
- Temperature range of material:** -30°C to 100°C, intermittent up to approx. 120°C
- Voltage:** 690 V
- Material:** Polypropylene, reinforced glass fibre; sealing: thermoplastic elastomere
- Terminals/poles:** 6 mm²
- Fixing:** 4 internal openings outside of the sealing area
- Equipment:**
- COMBI INDUSTRY with flat cover
 - Elastic self-sealing membranes for cable entry without mechanical devices: 7 inlets at the side and 3 inlets in the base
 - 7 integrated M 25 threads, no locknuts necessary
 - 4 captive quick-release lid screws
 - .../ESKV = incl. 3 pcs. ESKV M 25 (*Sealing range 9 - 17 mm)
- Accessories:**
- DIN RAIL KIT 607: Rail TS 35 + Fixing material, WISKA-No. 10060361
 - EC 607 Earthing plate: WISKA No. 10101474

| Type | WISKA-No. RAL 7035 | | | | L x B x H external / open mm |
|--------------------|-----------------------|------|---------|--|------------------------------------|
| COMBI IND 607/leer | 10060537 | 3/27 | 3 - 17 | | 110 x 110 x 57 |
| COMBI IND 607/ESKV | 10060536 | 3/27 | 3 - 17* | | 110 x 110 x 57 |
| COMBI IND 607/5 | 10060519 | 3/27 | 3 - 17 | | 110 x 110 x 57 |