


**WISKA COMBI IP68 SET**



- Protection class to EN 60 529:** IP 68 to 1,5bar (170h)  
**Flame protection:** Glühdrahtprüfung 750°C gemäß EN 60695-2-11  
**Temperature range:** -5°C to 60°C  
**Voltage:** - 308: 400V  
 - 607 / 1010: 690 V  
 :  
**Material:** Polypropylene, reinforced glass fibre; Sealing: Thermoplastic elastomere; Fluid: Polyorganosiloxane  
**Terminals/poles:** - 308: 4mm<sup>2</sup>  
 - 607: 6mm<sup>2</sup>  
 - 1010: 10mm<sup>2</sup>  
**Equipment:** - Existing COMBI boxes 308; 607 or 1010  
 - Plastic bag with fluid  
 - Plastic sprue

Type	WISKA-No.		 mm	L x B x H external / außen mm
COMBI IP68 SET	10060457	1	3 - 12	85 x 85 x 51
COMBI IP68 SET 308/5	10066634	1	3 - 12	85 x 85 x 51
COMBI IP68 SET 607	10061185	1	3 - 17	110 x 110 x 66
COMBI IP68 SET 607/5	10066635	1	3 - 17	110 x 110 x 66
COMBI IP68 SET 1010	10061488	1	6 - 21	140 x 140 x 82
COMBI IP68 SET 1010/5	10066636	1	6 - 21	140 x 140 x 82